

Product Summary


V_{DS} (V)	$R_{DS(on),max}$ (mΩ)	I_D (A)
60	1.6 @ $V_{GS} = 10V$	300 ⁽¹⁾

Features

- Low $R_{DS(on)}$ SGT technology
- Low thermal impedance
- Fast switching speed
- 100% avalanche tested

Application

- DC/DC conversion
- Power switch
- Motor drives



TOLL

NOTE:
 LOGO - GS
 GMXXXXX- Part number code
 F - Fab location code
 A - Assembly location code
 Y - Year code
 WW - Week code
 L&T - Assembly lot code

General Information


Shipping

- ❖ One shipping options is offered as standard
- ❖ Un-sawn wafer

Handling

- ❖ Product must be handled only at ESD safe workstations. Standard ESD precautions and safe work environments are as defined in MIL-HDBK-263.
- ❖ Product must be handled only in a class 10,000 or better-designated clean room environmen

Equivalent circuit



Absolute Maximum Rating ($T_a=25^\circ\text{C}$)

Parameter	Symbol	Limit	Unit
Drain-source voltage	V_{DS}	60	V
Gate-source voltage	V_{GS}	± 20	
Continuous drain current	I_D	$T_C=25^\circ\text{C}$ ⁽¹⁾	300
		$T_C=100^\circ\text{C}$	220
		$T_A=25^\circ\text{C}$ ⁽⁴⁾	31
Pulsed drain current ⁽²⁾	$I_{D,pulse}$	1100	
Avalanche energy, single pulse ⁽³⁾	E_{AS}	625	mJ
Power dissipation	P_D	$T_C=25^\circ\text{C}$	300
		$T_A=25^\circ\text{C}$ ⁽⁴⁾	2.9
Operating junction and storage temperature range	T_J, T_{stg}	-55 to 150	$^\circ\text{C}$

**Electrical characteristics (Ta=25°C ± 3°C)**

Parameter	Symbol	Test conditions	Min.	Typ.	Max.	Unit
Static parameter						
Drain to source breakdown voltage	V _{(BR)DSS}	V _{GS} = 0 V, I _D = 1 mA	60			V
Gate-source threshold voltage	V _{GS(th)}	V _{DS} = V _{GS} , I _D = 250 μA	1.7	2.5	3.3	V
Gate-body leakage	I _{GSS}	V _{DS} = 0 V, V _{GS} = ±20 V			±100	nA
Zero gate voltage drain current	I _{DSS}	V _{DS} = 100 V, V _{GS} = 0 V			1	μA
Drain-source on-resistance	R _{DS(on)}	V _{GS} = 10 V, I _D = 100 A		1.2	1.6	mΩ
Forward transconductance ⁽⁵⁾	g _{fs}	V _{DS} = 5 V, I _D = 100 A		121		S
Gate resistance	R _g	f = 1 MHz		2		Ω
Dynamic ⁽⁵⁾						
Total gate charge	Q _g	V _{DS} = 30 V, I _D = 30 A, V _{GS} = 10 V		142		nC
Gate-source charge	Q _{gs}			28		
Gate-drain charge	Q _{gd}			47		
Turn-on delay time	t _{d(on)}	V _{DS} = 30 V, I _D = 100 A, V _{GS} = 10 V, R _{GEN} = 6 Ω		16		ns
Rise time	t _r			88		
Turn-off delay time	t _{d(off)}			36		
Fall time	t _f			26		
Input capacitance	C _{iss}	V _{DS} = 30 V, V _{GS} = 0 V, f = 1 MHz		7450		pF
Output capacitance	C _{oss}			1680		
Reverse transfer capacitance	C _{rss}			90		
Reverse Diode Characteristics ⁽⁵⁾						
Diode forward voltage	V _{SD}	V _{GS} = 0 V, I _F = 100 A		0.8	1.1	V
Reverse recovery time	t _{rr}	V _{DS} = 30 V, I _F = 50 A, di/dt = 100 A/μs		79		ns
Reverse recovery charge	Q _{rr}			180		nC

Notes

- (1) Limited by maximum junction temperature..
- (2) Pulse width limited by maximum junction temperature.
- (3) $V_{DS} = 50\text{ V}$, $V_{GS} = 10\text{ V}$, $L = 0.5\text{ mH}$.
- (4) $R_{\theta JA}$ is determined with the device mounted on a 1 in² pad 2 oz copper pad on a 1.5x1.5 in. board of FR-4 material.
- (5) Guaranteed by design, not subject to production testing.

Thermal Characteristic (Ta=25°C)

Parameter		Symbol	Max.	Unit
Thermal resistance, junction-to-case	Steady state	$R_{\theta JC}$	0.5	°C/W
Thermal resistance, junction-to-ambient ⁽⁴⁾	Steady state	$R_{\theta JA}$	43	

Electrical characteristics diagrams

Typical Characteristics




Fig1. Typical output characteristics




Fig2. Typical $V_{GS(TH)}$ gate-source voltage Vs. T_j




Fig3. Typical transfer characteristics




Fig4. Typical normalized on-resistance Vs. T_j




Fig5. Typical on resistance Vs gate-source voltage




Fig6. Typical on resistance Vs drain current




Fig7. Typical source-drain diode forward voltage




Fig8. Maximum safe operating area




Fig9. Typical capacitance Vs. drain-source voltage




Fig10. Typical gate charge Vs. gate-source voltage




Fig11. Power dissipation Vs. case temperature










Fig12. Maximum drain current Vs. case temperature


Fig13. Typical $V(BR)DSS$ Vs T_j

Fig14. Maximum avalanche energy vs temperature ($^{\circ}C$)

Fig15 . Normalized maximum transient thermal impedance

Fig16. Unclamped inductive test circuit and waveforms

Fig17. Switching time test circuit and waveforms

Package outline dimensions: TOLL


Dim	Millimeters		
	Min	Nom	Max
A	2.20	-	2.40
b	0.70	-	0.90
b1	9.70	-	9.90
b2	1.20 REF		
c	0.40	-	0.60
D	10.28	-	10.48
D1	4.08	-	4.28
D2	3.20	-	3.40
D3	3.16	-	3.36
E	9.80	-	10.00
E1	8.40	-	8.60
E2	9.30	-	9.50
E3	8.80 REF		
E4	0.25	-	0.45
e	1.20 BASIC		
H	11.58	-	11.78
H1	7.23	-	7.43
H2	2.45 REF		
i	0.10	-	-
j	0.45 REF		
L	1.60	-	2.10
L1	0.60	-	0.80
L2	0.50	-	0.70
L3	1.05	-	1.30
ø	10° REF		

Important Notice

The information given in this document shall be for illustrative purposes only and shall in no event be regarded as a guarantee of conditions or characteristics. Gostone reserves the right to change any information herein. With respect to any examples, hints or any typical values stated herein and/or any information regarding the application of the product, Gostone or its affiliates hereby make no representation or warranty of any kind, expressed or implied, as to any information provided hereunder, including without limitation as to the accuracy, completeness or non-infringement of intellectual property rights of any third party, and they assume no liability for the consequences of use of such information. In addition, any information given in this document is subject to customer's compliance with its obligations stated herein and any applicable legal requirements, norms and standards concerning customer's products and any use of the product of Gostone in customer's applications. The information contained herein is exclusively intended for technically trained staff. No license is granted by implication under any patent right, copyright, mask work right, or other intellectual property right. It is customer's sole responsibility to evaluate the suitability of the product for the intended application and the completeness of the product information given herein with respect to such application. In no event shall Gostone or its affiliates be liable to any party for any direct, indirect, special, punitive, incidental or consequential damages of any nature whatsoever, including but not limited to loss of profits and loss of goodwill, whether or not such damages are based on tort or negligence, warranty, breach of contract or any other legal theory. In addition, any recipient of this document and the relevant products samples may not alter, decompile, disassemble, reverse engineer, or otherwise modify any information/samples received hereunder. Any intellectual property rights arising from the reverse engineering of Gostone's products shall belong to Gostone.