

Product Summary

V_{DS} (V)	$R_{DS(on),max}$ (mΩ)	I_D (A)
200	10.0 @ $V_{GS} = 10V$	110 ⁽¹⁾

Features

- Low $R_{DS(on)}$ SGT technology
- Low thermal impedance
- Fast switching speed
- 100% avalanche tested

Application

- DC/DC conversion
- Power switch
- Synchronous Rectification in SMPS


General Information

Shipping

- ❖ One shipping options is offered as standard
- ❖ Un-sawn wafer

Handling


- ❖ Product must be handled only at ESD safe workstations. Standard ESD precautions and safe work environments are as defined in MIL-HDBK-263.
- ❖ Product must be handled only in a class 10,000 or better-designated clean room environmen



TOLL

NOTE:
 LOGO - GS
 GMXXXXX- Part number code
 F - Fab location code
 A - Assembly location code
 Y - Year code
 WW - Week code
 L&T - Assembly lot code

Equivalent circuit



Absolute Maximum Rating ($T_a=25^\circ\text{C}$)

Parameter		Symbol	Limit	Unit
Drain-source voltage		V_{DS}	200	V
Gate-source voltage		V_{GS}	±20	
Continuous drain current	$T_C=25^{\circ}\text{C}$ ⁽¹⁾	I_D	110	A
	$T_C=100^{\circ}\text{C}$		78	
Pulsed drain current ⁽²⁾		$I_{D,pulse}$	440	
Avalanche energy, single pulse ⁽³⁾		E_{AS}	1440	mJ
Power dissipation	$T_C=25^{\circ}\text{C}$	P_D	333	W
	$T_A=25^{\circ}\text{C}$ ⁽⁴⁾		167	
Operating junction and storage temperature range		T_J, T_{stg}	-55 to 150	°C

Electrical characteristics (Ta=25°C ± 3°C)

Parameter	Symbol	Test conditions	Min.	Typ.	Max.	Unit
Static parameter						
Drain to source breakdown voltage	V _{(BR)DSS}	V _{GS} = 0 V, I _D = 1 mA	200			V
Gate-source threshold voltage	V _{GS(th)}	V _{DS} = V _{GS} , I _D = 250 μA	2.5	3.4	4.5	V
Gate-body leakage	I _{GSS}	V _{DS} = 0 V, V _{GS} = ±20 V			±100	nA
Zero gate voltage drain current	I _{DSS}	V _{DS} = 100 V, V _{GS} = 0 V			1	μA
Drain-source on-resistance	R _{DS(on)}	V _{GS} = 10 V, I _D = 100 A		8.3	10	mΩ
Forward transconductance ⁽⁵⁾	g _{fs}	V _{DS} = 5 V, I _D = 100 A		50		S
Gate resistance	R _g	f = 1 MHz		3.0		Ω
Dynamic ⁽⁵⁾						
Total gate charge	Q _g	V _{DS} = 100 V, I _D = 20 A, V _{GS} = 10 V		45		nC
Gate-source charge	Q _{gs}			30		
Gate-drain charge	Q _{gd}			13		
Turn-on delay time	t _{d(on)}	V _{DS} = 100 V, I _D = 20 A, V _{GS} = 10 V, R _{GEN} = 3 Ω		13		ns
Rise time	t _r			29		
Turn-off delay time	t _{d(off)}			37		
Fall time	t _f			31		
Input capacitance	C _{iss}	V _{DS} = 100 V, V _{GS} = 0 V, f = 1 MHz		2996		pF
Output capacitance	C _{oss}			462		
Reverse transfer capacitance	C _{rss}			13		
Reverse Diode Characteristics ⁽⁵⁾						
Diode forward voltage	V _{SD}	V _{GS} = 0 V, I _F = 2.0 A		0.7	1.2	V
Reverse recovery time	t _{rr}	I _F = 20 A, di/dt = 100 A/μs		124		ns
Reverse recovery charge	Q _{rr}			644		nC

Notes

- (1) Limited by maximum junction temperature..
- (2) Pulse width limited by maximum junction temperature.
- (3) $V_{DS} = 100\text{ V}, V_{GS} = 10\text{ V}, L = 1.0\text{ mH}$.
- (4) Device mounted on FR-4 substrate PC board with 2oz copper in 1inch square cooling area.
- (5) Guaranteed by design, not subject to production testing.

Thermal Characteristic (Ta=25°C)

Parameter		Symbol	Max.	Unit
Thermal resistance, junction-to-case	Steady state	$R_{\theta JC}$	0.35	°C/W
Thermal resistance, junction-to-ambient ⁽⁴⁾	Steady state	$R_{\theta JA}$	31	

Electrical characteristics diagrams




Figure 1: Output Characteristics




Figure 2: Transfer Characteristics




Figure 3: On-Resistance vs. Gate-Source Voltage




Figure 4: On-Resistance vs. Gate-Source Voltage




Figure 5: On-Resistance vs. Junction Temperature




Figure 6: Source-Drain Diode Forward Voltage




Figure 7: Gate Threshold Variation vs. Junction Temperature




Figure 8: Gate Charge Characteristics




Figure 9: Capacitance Characteristics




Figure 10: Power Derating




Figure 11: Current Derating




Figure 12: Safe Operating Area





Figure 13: Normalized Maximum Transient Thermal Impedance

Package outline dimensions: TOLL


Dim	Millimeters		
	Min	Nom	Max
A	2.20	-	2.40
b	0.70	-	0.90
b1	9.70	-	9.90
b2	1.20 REF		
c	0.40	-	0.60
D	10.28	-	10.48
D1	4.08	-	4.28
D2	3.20	-	3.40
D3	3.16	-	3.36
E	9.80	-	10.00
E1	8.40	-	8.60
E2	9.30	-	9.50
E3	8.80 REF		
E4	0.25	-	0.45
e	1.20 BASIC		
H	11.58	-	11.78
H1	7.23	-	7.43
H2	2.45 REF		
i	0.10	-	-
j	0.45 REF		
L	1.60	-	2.10
L1	0.60	-	0.80
L2	0.50	-	0.70
L3	1.05	-	1.30
θ	10° REF		

Important Notice

The information given in this document shall be for illustrative purposes only and shall in no event be regarded as a guarantee of conditions or characteristics. Gostone reserves the right to change any information herein. With respect to any examples, hints or any typical values stated herein and/or any information regarding the application of the product, Gostone or its affiliates hereby make no representation or warranty of any kind, expressed or implied, as to any information provided hereunder, including without limitation as to the accuracy, completeness or non-infringement of intellectual property rights of any third party, and they assume no liability for the consequences of use of such information. In addition, any information given in this document is subject to customer's compliance with its obligations stated herein and any applicable legal requirements, norms and standards concerning customer's products and any use of the product of Gostone in customer's applications. The information contained herein is exclusively intended for technically trained staff. No license is granted by implication under any patent right, copyright, mask work right, or other intellectual property right. It is customer's sole responsibility to evaluate the suitability of the product for the intended application and the completeness of the product information given herein with respect to such application. In no event shall Gostone or its affiliates be liable to any party for any direct, indirect, special, punitive, incidental or consequential damages of any nature whatsoever, including but not limited to loss of profits and loss of goodwill, whether or not such damages are based on tort or negligence, warranty, breach of contract or any other legal theory. In addition, any recipient of this document and the relevant products samples may not alter, decompile, disassemble, reverse engineer, or otherwise modify any information/samples received hereunder. Any intellectual property rights arising from the reverse engineering of Gostone's products shall belong to Gostone.